

PID	DESC	11/4/2020	11/6/2020	11/11/2020	11/12/2020	11/13/2020	11/16/2020	11/17/2020
02	DTC	P0301	P0301	P0301	P0301	P0301	P0301	P0301
03	Fuel system status	Closed Loop	Closed Loop	Closed Loop	Closed Loop	Closed Loop	Closed Loop	Closed Loop
04	Calc Eng Load (%)	74.5	48.6	93.3	49	47.1	0.8	73.7
05	Coolant Temp	59	72	79	73	82	73	90
06	STFT B1	-9.4	-14.1	-2.3	-9.4	-3.9	-6.2	1.6
07	LTFT B1	-1.6	-0.8	3.1	-0.8	-0.8	0	2.3
0C	RPM	1821	1046	1991	1730	1101	1178	2243
0D	Speed	7	17	15	10	0	0	10
0E	#1 timing Adv	23	26	10.5	42	3	5	23
0F	Intake temp	48	59	66	54	59	59	59
10	Mass air flow	2	0.7	3	1.3	0.7	0.7	2.5
11	Abs Thrott	22	17.6	27.5	19.6	17.6	17.6	23.5
15	O2 B1S2 Volt	0.055	0.055	0.055	0.055	0.055	0.055	0.055
15	O2 B1S2 STFT	99.2	99.2	99.2	99.2	99.2	99.2	99.2
1F	run time	43	41	44	46	48	47	48
24	B1S1 ratio	0.979	0.965	1.026	0.995	1.005	1.001	0.993
24	B1S1 Volt	3.183	3.075	0	3.261	3.324	3.3	0
2E	Com Evap Purge	0	0	0	0	0	0	0
30	#warm ups	4	5	13	3	2	2	6
31	Distance	18	40	60	18	6	9	25
33	Bar Press	30.1	29.8	29.8	29.5	29.5	29.5	29.5
34	B1S1 Current	-0.07	-0.137	0.023	-0.023	0.012	0	-0.027
34	B1S1 ratio	0.979	0.965	1.026	0.995	1.005	1.001	0.993
3C	B1S1 Cat temp	558.7	580.6	579	617	549	546.1	538.7
3E	B1S2 Cat Temp	60.6	86.9	84.9	75.6	75.9	69.3	81.9
42	Cntrl Volt	14.062	14.042	14.042	14.062	13.906	14.003	14.042
43	abs load	45.5	29.8	64.3	31	26.7	25.9	47.1
44	Com Ratio	0.999	0.999	0.999	0.999	0.999	0.999	0.999
45	Rel throt	3.1	0	8.6	0.8	0	0	4.7
47	Abs Throt B	54.9	49.8	62	52.2	49.4	49.8	56.9
49	Acc Ped D	22	15.7	26.3	20.4	15.7	15.7	23.1
4A	Acc Ped E	38	32.2	42.4	36.1	32.2	32.2	39.2
4C	Com Throt act	22	17.6	27.8	19.6	17.6	17.6	23.1
4E	time since cleared	72	128	243	76	49	41	103
53	Abs evap press	411.92	409.97	406.7	405.12	403.53	405.82	402.99