

Sensor Name	Value	Units	Minimum	Maximum	Range	
Calculated Load	99	%	0	100		99 %
Short Term Fuel Trim Bank One	0.00	%	-100.00	99.22		50 %
Short Term Fuel Trim Bank Two	0.00	%	-100.00	99.22		50 %
Long Term Fuel Trim Bank One	5.46	%	-100.00	99.22		52 %
Long Term Fuel Trim Bank Two	5.46	%	-100.00	99.22		52 %
Engine RPM	2102	r/min	0	9000		23 %
Air Flow Rate From Mass Air Flow Sensor	7.96	lb/min	0.00	86.70		9 %
Calculate Load	100.0	%	0.0	100.0		99 %
B1S1 Catalyst Temperature	1048.10	F	-40.00	11756.30		9 %
B1S2 Catalyst Temperature	1048.10	F	-40.00	11756.30		9 %
B2S1 Catalyst Temperature	836.60	F	-40.00	11756.30		7 %
B2S2 Catalyst Temperature	836.60	F	-40.00	11756.30		7 %
MAF	60.31	gm/s	0.00	655.35		9 %

☐ Sensor Name	Sensor Grouping	
☐ VVT Change Angle #2	EnhancedPowertrain234CAN	
☒ Cylinder #1 Misfire Count	EnhancedPowertrain234CAN	
☐ Cylinder #2 Misfire Count	EnhancedPowertrain234CAN	
☐ Cylinder #3 Misfire Count	EnhancedPowertrain234CAN	